



BEARING FORGE OF AMERICA CORP.



10 mm x 26 mm x 8 mm skf 6000 bearing

Bearing No. 6000

| | |
|-------------------------------|--------------------------|
| Size | 10x26x8 mm |
| Bore Diameter | 10 mm |
| Outer Diameter | 26 mm |
| Width | 8 mm |
| d | 10 mm |
| D | 26 mm |
| B | 8 mm |
| C | 8 mm |
| d1 | 14,8 mm |
| r1 min. | 0,3 mm |
| r2 min. | 0,3 mm |
| D1 | 21,2 mm |
| D2 | 22,6 mm |
| da min. | 12 mm |
| Da max. | 24 mm |
| rc max. | 0,3 mm |
| Weight | 0,019 Kg |
| Basic dynamic load rating (C) | 4,75 kN |
| Basic static load rating (C0) | 1,96 kN |
| Fatigue load limit (Pu) | 0,083 |
| Reference speed | 67000 r/min |
| Limiting speed | 40000 r/min |
| Calculation factor (f0) | 12 |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |

6000 Bearing 2D drawings and 3D CAD models



BEARING FORGE OF AMERICA CORP.

| | |
|---------------------------------|---|
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.02 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 10MM Bore; 26MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 6000 |
| Weight / LBS | 0.05 |
| Outside Diameter | 1.024 Inch 26 Millimeter |
| Bore | 0.394 Inch 10 Millimeter |
| Outer Race Width | 0.315 Inch 8 Millimeter |
| d ₁ | 14.8 mm |
| D ₂ | 22.6 mm |
| r _{1,2} min. | 0.3 mm |
| | |



BEARING FORGE OF AMERICA CORP.

| | |
|--------------------------------|----------|
| d_a min. | 12 mm |
| D_a max. | 24 mm |
| r_a max. | 0.3 mm |
| Basic dynamic load rating C | 4.75 kN |
| Basic static load rating C_0 | 1.96 kN |
| Fatigue load limit P_u | 0.083 kN |
| Calculation factor k_r | 0.025 |
| Calculation factor f_0 | 12 |
| Mass bearing | 0.018 kg |